

ASA SPRAY

SAFETY DATA SHEET NON CHLORINATED ADHESIVE

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING.

PRODUCT NAME: ASA SPRAY

SUPPLIER: Lead'Air International s.a.

Chawieumont 22

B-4910 Theux (Belgium)

EMERGENCY TELEPHONES: 0032(0)87-530600

0032(0)87-530604

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME	CAS NO.	EINECS	HEALTH (class)	RISK (R No.)	CONTENTS %
Acetone Heptane & Isomers Hexane, Mixture of Isomers	67-64-1	200-662-2	F Xi F Xn Xi F Xn XI	`R11 ´ R11 R11	10-30 5-10 1-5
Methylcyclohexane Pentane Solvent Naphtha, Light Aromatic, <0.1% Benzene	108-87-2 109-66-0 64742-95-6	203-624-3 203-692-4	F Xn Xi F Xn Xn XI	R11 R12 R11	<1 <1 1-5
Butane Propane	106-97-8 74-98-6	203-448-7 200-827-9	FX FX	R12 R12	

The full texts for all R – Phrases are displayed in section 15.

3. HAZARDS IDENTIFICATION

Extremely flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on a naked flame of any other incadesent material – NO SMOKING

4. FIRST AID MEASURES

INHALATION:	Remove the exposed person immediately to fresh air, keep the patient warm and at rest. If breathing is irregular or has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position. Get prompt medical attention.
INGESTION:	Rinse mouth thoroughly. Do not induce vomiting. Get medical attention immediately.
SKIN:	Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if irritation persists after washing.
EYES:	Contact lenses should be removed. Promptly wash eyes

and get medical attention.

with water for at least 15 minutes holding eyelids apart

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Fire can be extinguished using: Powder, foam or carbon

dioxide (C02).

UNUSAL FIRE & EXPLOSION

HAZARDS: Unstable. May explode spontaneously. Possible

container rupture.

SPECIAL FIRE FIGHTING

PROCEEDURES: Use water SPRAY only to cool containers! Do not put

water on leaked material. If possible, fight fire from

protected position.

SPECIFIC HAZARDS Toxic gases/vapours/fumes of carbon dioxide (CO2).

Carbon monoxide (CO).

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION Avoid breathing vapour, ensure adequate

IN SPILL: ventilation. Avoid skin and eye contact. Wear personal

protective equipment.

PRECAUTIONS TO PROTECT

THE ENVIRONMENT:

Prevent entry into drains and watercourses.

SPILL CLEANUP METHODS: Extinguish all sources of ignition. Avoid sparks, flames,

heat and smoking. Ventilate. Absorb onto sand, earth or absorbent granules. Pick up with non sparking tools & place into metal containers with sealable lids. Mark the containers with details of hazards and store in

designated areas ready for disposal.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Keep away from heat, sparks and open flame. Avoid

spillage, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air

contamination is above acceptable level.

STORAGE PRECAUTIONS: Flammable/combustible – keep away from oxidisers,

heat, sparks and open flames. Store at moderate temperatures in dry, well ventilated area. Aerosol cans: Must not be exposed to direct sunlight or temperatures

above 50°C.

8.EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME CAS. No: EINECS STD LT EXP 8hrs ST EXP 15Mi

Acetone









VENTILATION: Provide adequate ventilation to ensure the airborne

concentration does not exceed the above levels. Ensure

there are no sources of ignition.

RESPIRATOR PROTECTION: Adequate respiratory protection must be used if air

concentration exceeds acceptable level.

HAND PROTECTION: Protective gloves must be used if there is risk of direct

contact or splash. Use protective gloves made of: Nitrile.

EYE PROTECTION: Wear splash proof goggles to prevent any possibility of

eye contact.

SKIN PROTECTION: Wear appropriate clothing to prevent repeated or

prolonged skin contact.

HYGIENIC WORK PRACTICES: Wash promptly if skin becomes contaminated. Wash at

the end of each work shift and before eating, smoking

and using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Aerosol COLOUR: Clear

ODOUR/TASTE: hydrocarbons/Solvent Can pressure 70psi

BOILING POINT (°C, INTERVAL): 40
DENSITY/SPECIFIC GRAVITY (v/ml) 0.8

SOLUBILITY DESCRIPTION: Slightly soluble in water. Soluble in: solvents.

FLASH POINT (°C): - 40 (propellant)

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions. Stable at room

temperature.

CONDITIONS TO AVOID: Heat. Hot surfaces. Sources of ignition. Flames.

MATERIAL TO AVOID: Strong oxidising agents. Strong acids and strong alkalis.

HAZ. DECOMP. PRODUCTS: In combustion emits toxic fumes of carbon dioxide/

carbon monoxide. In combustion emits toxic fumes of

hydrogen cyanide.

11.TOXICOLOGICAL INFORMATION

INHALATION: Drowsiness, dizziness, disorientation, vertigo.

INGESTION: May cause discomfort if swallowed.

SKIN: Liquid may irritate skin.

EYES: Irritation, burning, lachrymation, blurred vision after liquid

splash.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Dangerous for the environment: May cause long term

adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Dispose of in accordance with Local Authority

requirements. Empty containers must not be burned

because of explosion hazard.

14. TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



UN No. ROAD: 1950 UK ROAD TRANSPORT CLASS: 2.1

UK ROAD PACK GR.: Not Applicable

ADR CLASS No.: 2
ADR CLASS: 2

ADR PACK GR.: Not Applicable

ADR LABEL No.: 2.1

PROPER SHIPPING NAME: AEROSOLS

RID CLASS No.: 2

RID CLASS GR.: Not Applicable

UN No. SEA: 1950 **IMDG CLASS:** 2.1

IMDG PACK GR.:

EmS No.:

F-D,S-U

MARINE POLLUTANT:

UN No. AIR:

ICAO CLASS:

AIR SUB CLASS:

2.1

AIR PACK GR.: Not Applicable

15.REGULATORY INFORMATION

LABEL FOR SUPPLY:







Extremely Flammable

RISK PHRASES:	R12	Extremely Flammab
RISK PHRASES:	R12	Extremely Flammab

R51/53 Toxic to aquatic organisms, may cause

long term adverse effects in the aquatic

environment

R67 Vapours may cause drowsiness and

dizziness

SAFETY PHRASES: S2 Keep out of reach of children.

S9 Keep container in well ventilated place. S16 Keep away from sources of ignition – No

Smoking.

Lead'Air International October 09

S23 Do not breathe vapour/spray.

S29/56 Do not empty into drains, dispose of

material and its container at hazardous or special waste collection points.

S36/37/39 Wear suitable protective clothing, gloves

and eye/face protection.

S38 In case of insufficient ventilation, wear

suitable respiratory equipment.

S51 Use only in well ventilated areas.

S61 Avoid release to the environment. Refer

to special instructions/safety data sheets

16. OTHER INFORMATION

USER NOTES: For further information consult the product data sheet or

contact Technical Services.

APPLICATION EVALUATION: An evaluation of the adhesive should be carried out in

application conditions before commercial use is undertaken. This should also include a reference to

ageing.

LIMITATIONS: This product is not suitable for highly plasticised PVC.

CAUTION: Pressurised container. Do not expose to temperatures

exceeding 50°C. Protect from sunlight. Do not puncture or incinerate even when empty. Do not spray onto naked

flame or any incandescent material.

INFORMATION SOURCES: This safety data sheet was compiled using current safety

information supplied by distributor of raw materials.

REVISION COMMENTS: This safety data sheet supersedes all previous issues

and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact

Lead'Air International s.a.

ISSUE: E/1

REVISION DATE: September 2005

This advice is given by Lead'Air International who accept no legal liability for it. The information herein is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It should not therefore, be construed as guaranteeing specific properties.